

FEATURES

- Best picture quality (in combination with Digital LCD monitor)
- High resolution CCD camera (470,000 pixels)
- 1/3" Color CCD high resolution image sensor
- IP69K Waterproof Rating
- Diagonal 130° Viewing
- Normal/Mirror Image switching
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone
- Built-in IR LED's
- Built-in Automatic Heater (below +10°C)
- Temp. -40°C ~ 80°C
- Vibration resistant
- Waterproof screw type connector (IP67), 4-pin mini-DIN.
- E-mark.
- ADR approved cable (UV-resistant, resistant to cold temperatures, resistant to most oils, chemicals and weather conditions; meets ISO 4141 and DIN/ISO 6722)



Specifications

| | |
|------------------------------|---|
| Image Sensor | 1/3" Color SONY SUPER HAD II CCD |
| Scanning System | PAL 470,000 pixels |
| Resolution | 520 TV Lines |
| S/N ratio | Minimum 44dB (at AGC off) |
| Minimum Illumination | 0 lux (IR LED's on) |
| Power supply | DC 9 ~ 28V |
| Power Consumption | DC 12V, 325mA (Heater on) DC 12V, 110mA (Heater off) |
| Operating Temperature | -40°C to +80°C |
| Field of View angle | 130° (Diagonal), 96.2° (Horizontal), 69° (Vertical) |
| Dimension | 102(W) x 43(H) x 63(D) mm (camera only) 124(W) x 85(H) x 80(D) mm (incl. bracket & sunvisor) |
| Weight | 326g (total weight incl. bracket & sunvisor: 464g) |